

DeWAL® DW950-56 Laminate

DeWAL® DW950-56 is a laminate of 0.013 cm (0.005") PTFE film and 0.127 cm (0.035") polyethylene foam. Used as a cap liner for sealing liquids into an enclosure, DeWAL DW950 series products are highly chemically-resistant, provide great durability, and can resist a wide range of environmental conditions providing confidence that even dangerous chemicals are controlled and safely contained.

Select DeWAL DW950 products can be used for biological, pharmaceutical, and high purity water containers in addition to industrial and household applications. All DW950 series products are PFOA free.



TECHNICAL DATA	TEST METHOD	RESULTS
PHYSICAL		
Total Laminate Thickness, cm (inches)	ASTM D6040	0.14 (0.055)
Base Film	N/A	PTFE
Peel Adhesion, g/cm (oz/in)	ASTM D3330	502.25 (45)
Foam Thickness, cm (inches)	ASTM D6040	0.127 (0.050)
PTFE Thickness, cm (inches)	ASTM D6040	0.013 (0.005)
PACKAGING SPECIFICATIONS	METRIC	ENGLISH
Width cm, inches	1.588 to 45.72	0.625 to 18
Max Roll O.D. cm, inches	35.56	14
Core I.D. cm, inches	7.62, 15.24, 20.32	3, 6, 8

* DW950-56 is listed on Drug Master File #17137 filed with the FDA and can be referenced upon authorization. The PTFE film is compliant to 21CFR177.1550 and passes EU 10/2011 migration tests for food contact.

All metric conversions are approximate.

Additional technical information is available.

Typical values should not be used for specification limits.