



ROLINX[®] Thermal

Product Information

ROLINX[®] Thermal is Rogers' solution to respond to an increasing demand for higher power levels in power converters. More power density is reflected in a need for higher working temperatures while copper thickness should remain stable.

While other laminated busbars (ROLINX Easy and Performance) are limited to a working temperature of 105°C, ROLINX Thermal allows increased working temperatures up to 130°C. This results in a unique advantage by upgrading the current system design to a higher power level.

ROLINX Thermal meets the highest humidity conditions. The extended conditions are 85°C / 95% RH, while the standard conditions are 55°C / 95% RH. Upon the requirements of the program, the customer can choose the appropriate humidity conditions for the ROLINX Thermal.

Rogers developed a proprietary Nickel formulation "Tex Nickel" specifically for higher temperature environments, enhancing/assuring smooth process capabilities while guaranteeing both visual and functional quality.

Advantages

- // Developed to get more power from the existing system and design
- // Extended thermal characteristics: up to 130°C
- // Extended humidity rating
- // Designed to last



Typical Market Segments

- // Traction (railway, ship propulsion, mining vehicles and other heavy equipment)
- // Industrial converters
- // Clean energy
- // Electricity production



Typical Technical Characteristics

Voltage	12 kV DC
Power	up to several MW
Temperature range	- 50°C / + 130°C
Relative humidity	55°C / 95% RH (standard); 85°C / 95% RH (extended)
Conductor material	Copper, Aluminium
Insulation material	Polyester dielectric film, rigid insulation board
Production test	Partial discharge, high voltage, dimensional

Rogers BVBA

Power Electronics Solutions - ROLINX
Afrikalaan 188
9000 Gent
Belgium
Phone +32 9 235 36 - 11
Fax +32 9 235 36 - 58

Rogers Technology (Suzhou) Co., Ltd.

No. 18 West Shenhu Road
Suzhou Industrial Park
Suzhou, PRC, 215122
Phone +86 512 62 58 - 2700
Fax + 86 512 62 58 - 2858

europe@rogerscorp.com
www.rolinx.com
www.rogerscorp.com/pes

The information contained in this document is intended to assist you in designing with Rogers' Power Electronics Solutions Materials. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown in this document will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers ROLINX Busbars for each application. The Rogers logo, the ROLINX logo and ROLINX are trademarks of Rogers Corporation or one of its subsidiaries.