

DeWAL® DW 750

Pressure sensitive tape produced from a black UHMW polyethylene film with an aggressive acrylic adhesive.

Suitable for chute liners, wear pads, and guide rails. Also suitable for anti-squeak and sound deadening in automotive applications.

- Non-stick surface
- Low friction
- High tensile strength
- Abrasion resistant

PROPERTY	TEST METHOD	750-3	750-5	750-10	750-20
PHYSICAL					
Backing Material		UHMW Film	UHMW Film	UHMW Film	UHMW Film
Backing Thickness, inches, (mm)	ASTM-D374	0.003 (0.080)	0.005 (0.13)	0.010 (0.25)	0.020 (0.50)
Adhesive System		Acrylic	Acrylic	Acrylic	Acrylic
Adhesive Thickness, inches, (mm)	ASTM-D374	0.0023 (0.058)	0.0023 (0.058)	0.0023 (0.058)	0.0023 (0.058)
Adhesion Strength to Steel, oz/in, (g/cm)	ASTM-D1000	65 (725)	75 (837)	75 (837)	65 (725)
	ASTM-D3759/882	20 (3572)	30 (5357)	60 (10715)	120 (21430)
Elongation,%	ASTM-D3759/882	300	300	300	300
Maximum Operating Temperature, °F, (°C)		200 (93)	200 (93)	200 (93)	200 (93)
PACKING SPECIFICATIONS					
Maximum Width, inches, (mm)		26 (660)	26 (660)	26 (660)	26 (660)
Core Diameter, inches, (mm)		3 (76.2)	3 (76.2)	3 (76.2)	3 (76.2)
Roll Length, yards, (m)		18 (16.46)	18 (16.46)	18 (16.46)	18 (16.46)
Liner		White Paper	White Paper	White Paper	Blue Poly

All metric conversions are approximate.

Additional technical information is available.

Typical values should not be used for specification limits.