

## DeWAL® DW950-40 Laminates

DeWAL® DW950-40 is a laminate of 0.005" PTFE film and 0.035" polyethylene foam. DeWAL DW950 series products are highly chemically-resistant, provide lasting durability, and resist a wide range of environmental conditions, providing confidence that contents are controlled and safely contained.

DeWAL DW950-40 can be used in seals and closures for the biological, pharmaceutical, high purity water and chemical markets. DW950-40 is listed on DeWAL DMF #17137 currently filed with the FDA and all DW950 series products are PFOA free.



| TECHNICAL DATA           | TEST METHOD | RESULTS             | METRIC RESULTS         |
|--------------------------|-------------|---------------------|------------------------|
| Total Laminate Thickness | ASTM D6040  | " <u>ž</u> " 40 [ ž | " <i>]</i> #02 U_      |
| Base Film                | N/A         | BF87                | N/A                    |
| Peel Adhesion            | ASTM D3330  | &' al∄[ž            | '"\$ <b>2</b> \$' Y!U_ |
| Foam Thickness           | ASTM D6040  | " Ž 35 in.          | "ž089 U_               |
| PTFE Thickness           | ASTM D6040  | "Ž"5 [ ž            | " <i>ž</i> ' 13 U_     |

| PACKAGING SPECIFICATIONS | ENGLISH         | METRIC                    |
|--------------------------|-----------------|---------------------------|
| Width                    | 0.625 to 18 mil | 1.588 to 45.72 cm         |
| Max Roll O.D.            | 24 in.          | 60.96 cm                  |
| Core I.D.                | 3, 6, 8 in.     | 7.62 , 15.24, or 20.32 cm |

All metric conversions are approximate.

Additional technical information is available.

Typical values should not be used for specification limits.

