



DeWAL® DW950-50 Laminates

DeWAL® DW950-50 is a laminate of 0.010" PTFE film and 0.040" polyethylene foam. DeWAL DW950 series products are highly chemically-resistant, provide lasting durability, and resist a wide range of environmental conditions, providing confidence that contents are controlled and safely contained.

DeWAL DW950-50 is used as a lining for the cap and closure market. The product can be used in seals and closures for a wide range of solutions and chemicals including high purity water enclosures.

All DW950 series products are PFOA free.



TECHNICAL DATA	TEST METHOD	RESULTS	METRIC RESULTS
Total Laminate Thickness	ASTM D6040	0.050 in.	0.127 cm
Base Film		PTFE	N/A
Peel Adhesion	ASTM D3330	45 oz./in.	502.25 g/cm
Foam Thickness	ASTM D6040	0.040 in.	0.102 cm
PTFE Thickness	ASTM D6040	0.010 in.	0.025 cm

PACKAGING SPECIFICATIONS	ENGLISH	METRIC
Width	0.625 to 18 mil	1.588 to 45.72 cm
Max Roll O.D.	14 in.	35.56 cm
Core I.D.	3, 6, 8 in.	7.62, 15.24, or 20.32 cm

All metric conversions are approximate.
Additional technical information is available.
Typical values should not be used for specification limits.



The information contained in this Data Sheet is intended to assist you in designing with Rogers' Elastomeric Material Solutions. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown in this data sheet will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers DeWAL products for each application. The Rogers logo, DeWAL logo and DeWAL are trademarks of Rogers Corporation or one of its subsidiaries. © 2018, 2019 Rogers Corporation. All rights reserved. 0419-PDF • Publication #175-039