

GRISWOLD® Sponge Rubber Automotive Product Guide

Product	Hardness CFD in kPa (psi)	Specification	Typical Applications
3110	Soft 14 - 34 (2 - 5)		Non-Skid Bin Liners & Padding Under Leather Wrapping
AX3185	Medium 34 - 62 (5 - 9)	FMVSS 302	
3120	Medium 34 - 69 (5 - 10)		
3130	Medium Firm 69 - 110 (10 - 16)		
3097	Medium Firm 66 - 117 (9 - 17)	FMVSS 302	
3140	Firm 110 - 152 (16 - 22)		
3150	Extra Firm > 152 (> 22)		
3241	Extra Firm 138 - 276 (20 - 40)	FMVSS 302 SAE J1756	

The information contained in this statement is intended to assist you in designing with Rogers GRISWOLD® Sponge Rubber. It is not intended to and does not create any warranties, expressed or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown on the statement will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers' GRISWOLD Sponge Rubber for each application. The Rogers and Griswold logo are trademarks of Rogers Corporation or one of its subsidiaries. © 2018, 2019, 2020 Rogers Corporation. All rights reserved. Printed in U.S.A., 1220-PDF, Publication #203-088 www.rogerscorp.com